



Print at "actual size" or "100%".
Do not scale.
Print orientation : Auto

PATTERN SYMBOLS




NOTCHES indicate matching points of the pattern pieces.




Center Fold Line - snip or mark about 1/8" (3mm) on this line.

To ensure accuracy open the pattern
with Adobe Reader.
Free download at www.adobe.com/reader



1 inch



2 cm

test squares
(test your printer)

Watch the full video tutorial
<https://youtu.be/4ot3JnYRbB4>

Seam allowances are included in this pattern

2

Mini Makeup Pouch

Pocket
Cut 2x Mesh Fabric
www.yoansewingstudio.com

©Copyright 2024 YuanSewingStudio

NOTES

- After cutting each panel from the pattern pieces, immediately transfer and cut all the notches and marking lines.
- Pay close attention to the pattern pieces labeled with **"Top"**. Mark the **"Top"** of the fabric after cutting.
- If your fabric has directional print, do assessment before cutting to achieve the desired look.
- Watch the full instructions in the video tutorial <https://youtu.be/4ot3JnYRbB4>
- Share the pictures of your finished bag on instagram #yoansewingstudio

Mini Makeup Pouch Project Supplies

Fabric

- Exterior: 1/6 yard cotton quilting fabric or 1 fat quarter
- Interior: 1/6 yard cotton quilting fabric or 1 fat quarter
- Mesh fabric: 5 1/2" x 10" (14 x 25.5cm)

Batting & Interfacing

- 6 1/2" x 13" batting (16.5 x 33cm)
- 7" x 12" (18 x 30.5 cm) fusible woven interfacing

Zippers

- 1x Nylon coil zipper 12" (30.5cm) long; 1 1/4" (3.2cm) wide /#5 or #4.5

Other

- 3/4" (19mm) wide foldover elastic 10" (25.5cm) long
- Polyester thread
- 1/8" or 1/4" basting tape
- 3/4" single fold bias tape

Finished pouch measurements
 Approx. 5" wide (top) x 5" tall x 2 1/4" deep
 (12.7 x 12.7 x 5.7 cm)

Designed by: Yuan Zivkovic
 Skill Level: Advanced Beginner

Features
 Zipper closure
 2x Mesh pockets
 Loop handle

Mini Makeup Pouch Project Supplies

Name	Exterior Fabric	Lining Fabric	Batting/ Interfacing
Main Body (front&back)	Cut (2) - Pattern 1	Cut (2) - Pattern 1	Cut (2) batting - Pattern 1
Loop Handle	Cut (1) - 2" x 4" (5x10cm)		
Zipper Gusset	Cut (2) 1 3/4" w x 11 1/2" (4.5 x 29 cm)	Cut (2) 1 3/4" w x 11 1/2" (4.5 x 29 cm)	Cut (2) Interfacing 1 3/4" w x 11 1/2" (4.5 x 29 cm)
Lower/ bottom Gusset	Cut (1) 3" w x 9 1/2" (7.5 x 24 cm)	Cut (1) 3" w x 9 1/2" (7.5 x 24 cm)	Cut (1) Interfacing 3" w x 9 1/2" (7.5 x 24 cm)
Interior mesh pocket	Cut 2x mesh fabric, Pattern 2 Cut 2x fold over elastic 5" (12.7 cm) long		

Brief Directions

Seam allowances are 3/8" (cm) unless otherwise stated.

Please watch the [Full Video Tutorial](#) along side the below instructions for thorough demonstration, and to avoid any confusion.

Preparation

1. Fuse the fusible woven interfacing to the wrong side of the exterior zipper gusset panels according to the manufacturer's instructions.
2. Fuse the fusible woven interfacing to the wrong side of the exterior bottom gusset panel according to the manufacturer's instructions.

Exterior

3. Layer a batting piece to the wrong side of a main body panel, quilt as desired.
Repeat the same to the remaining main body & batting pieces. Trim off any excess batting.
4. Mark the center point of the top and bottom of each main body panel.
5. Sew and install the loop handle.

Interior

6. Bind the top edge of each mesh pocket panel with the foldover elastic.
7. Attach each mesh pocket panel on the right side of each interior main body panel.

Watch the full video tutorial
<https://youtu.be/4ot3JnYRbB4>

Zipper Gusset

8. Make the zipper gusset.
9. Trim off the front side so that the zipper gusset will measure 3" (7.5cm) wide.
10. Trim off any excess zipper.

Lower gusset, assembly, finish

11. Join the lower gusset panels to the zipper gusset.
12. Mark the center point of the zipper gusset and lower gusset. We will now call this panel the **gusset panel**.
13. With the wrong sides facing, sew the front exterior panel and the front interior panel with 1/4" (6mm) seam allowance.
14. With the wrong sides facing, sew the back exterior panel and the back interior panel with 1/4" (6mm) seam allowance.
15. With the right sides facing, sew the front side of the gusset to the front panel.
16. With the right sides facing, sew the back side of the gusset to the back panel.
17. Bind the raw edges to finish.

Terms of use: You may sell the pouch that you make with this pattern. Permission to sell is given for small scale home based handmade business.